
KEMET Part Number: PME295RB4330MR30

(P295BL332M440A)



Capacitor, Film, Metallized Paper, 3300 pF, +/-20% Tol, -40/+115C, Safety: Y1, 480 VAC, Lead Spacing=15 mm



	Dielectric:	Metallized Paper
	Application:	Safety: Y1
	Style:	Radial Box
	Lead Form:	Wire Leads
	Features:	Pulse
	Approvals:	ENEC,UL,cUL,CQC
	RoHS:	Yes
	Specifications	
_	•	

General Information
Supplier: | KEMET

Dimensions (mm)				
Symbol	Dimension	Tolerance		
L	18	MAX		
Н	14.5	MAX		
Т	7.5	MAX		
S	15	+/-0.4		
LL	30	+5		
G	0.5	NOM		
F	0.8	+/-0.05		

Specifications		
Capacitance:	3300 pF	
Voltage:	1500 VDC	
Tolerance:	+/-20%	
Voltage AC:	480 VAC	
Voltage:	440 VAC (ENEC)	
Rated Temperature:	115C	
Temperature Range:	-40/+115C	
Dissipation Factor @ 1 kHz:	1.3%	
Insulation Resistance:	12 GOhm	
Maximum dVdT:	2000 v/us	
Miscellaneous:	SRF= 27 MHz	

Packaging Specifications		
Package Kind:	Bulk	
Package Quantity:	400	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

