Brad[®] applicom[™] Serial Network Interface cards

PCI Universal, PCI Express

Quickly and easily connect your PC-based industrial applications to the industrial world with applicom[™] intelligent communication solutions

applicom[™] intelligent communication offers complete and ready-to-use solutions that cover more than 40 protocols within a wide choice of industrial networks and fieldbuses including Ethernet, Profibus, WorldFIP and Serial Links. These communication solutions connect PC-based applications (HMI, SCADA, MES, custom applications) to devices including programmable controllers, I/O modules, Panel PCs, process instruments and other industrial equipment.

With applicom[™] smart built-in processor technology, each network interface card (NIC) is able to execute all management and processing (polling, frame management, etc) of communication protocols without using a computer's processing (CPU) time; resulting in extremely fast, efficient application performance.

applicom[™] solutions are recommended for SCADA/HMI, and custom automation control systems which require powerful data acquisition to manage a large volume of I/O data. applicom[™] cards are successfully installed around the world in sectors as varied as oil and gas, automotive, food processing, technical building management, and transportation.

Eliminates data bottlenecks, ensuring delivery of

Provides all-in-one solution; guick development

and commissioning of applicom into system

Optimum choice for HMI/SCADA applications

time critical information

architectures

Features and Benefits

On-board co-processor for fast data acquisition between PC-based applications and industrial devices connected to Serial networks Integrated package includes all protocols; ONE configuration and ONE diagnostic tool whatever the protocols used

Combine several cards (up to 8) and run simultaneously from 1 to 32 protocols on a single PC

Applications

Supervision / Scada to monitor plant

HMI; Acquisition of process data on panel pc to manage complex machine

Active front-end acquisition for building management systems such as fire detection, access control, power distribution, HVAC

Measures and bench tests for process simulation, car engine validation, and experimental prototypes

Design tools for custom solutions such as a gateway feature, time table management, alarming, etc.

molex



Brad[®] applicom[™] Serial NIC

CE







Support of Windows[®] 8 and 2012 Server

Brad[®] applicom[™] Serial Network Interface cards

PCI Universal, PCI Express

molex

Specifications

PRODUCT PACKAGE

Engineering Tools Configuration console Test and diagnostic tools Data Servers OPC DA v3.0 and v2.05 Wonderware DAServer Wonderware I/O (SuiteLink/FastDDE) Includes Development Libraries Visual Studio (VB/C++/C samples) MS Visual Studio 2005 (.Net and C# samples) Installed on local disc Other unsupported samples (Borland Delphi, Windev and National Instruments (LabWindows CVI, LabVIEW/VI) on CD Rom only Supported OS: Windows (32-bit & 64-bit): 8, 2012 Server, 7, 2008 Server, Vista, 2003 Server, XP

COMMUNICATION PORTS

1x Serial Port D-Sub, 9pin, male 2 LEDs (TX/RX) 50 bps to 38.4 Kbps Electrical Interface RS485/RS422 with galvanic insulation (500 V)

TECHNICAL DATA

Bus Format PCI Universal bus 3.3V/5V (PCI-X compatible) PCI Express 1x AMD SC520 16 Mb SDRAM 4 Mb Flash Memory Interruption: Hardware Plug & Play DPRAM Address: Hardware Plug & Play Consumption: 5.5W Discrete Input: Opto-coupled discrete input, Voltage -> +10 to +30 DC or 24 V AC (50-60 Hz) Discrete Output: «Watchdog» output contact free from potential, (floating) (24V DC, 0.25A) Dimension: 168mm x 107mm

PROTOCOLS

Serial Allen-Bradley – DF1 Master GE Fanuc – SNP-X Master Elsag Bailey – Data Link Master Modbus Master / Slave (ASCII & RTU) Moller Group – SucomA Master Omron – Sysmac Way Master Saïa – S-Bus Master Siemens – 3964/3964R Master Siemens – AS511 Master Siemens – PPI/PPI+ Master Siemens – TI-Dir Master Schneider – Uni-Telway Master/Slave

CONFORMANCES

CE RoHS OPC Certified PCI Express certified Rockwell Encompass Schneider Collaborative

a harper that mean funct for two	N REI MEI M	(iii)e maar	(Brown	·@	Inputs Packet/s	Outputs Packet/s
And An Antonia State Sta	 → A EMPARIA Extension And successful and any (a) \$ 100 to 100 to 100 to 100 to (b) \$ 100 to 100 to 100 to 100 to (b) \$ 100 to 100 to 100 to 1	Sachuar Alfres Sachuar Bu abhra Sachuar Bug Law Lek ten Roda astero kegh Roda tanchi kegh Roda tanchi kegh	8.00% AUT CC IF AT DE DE AUT 3298 6 6 9 9 14 1100	Landard Renderic Land		
		A subry name Lineargenet high annon Cudget annon A subress anno		Ro To Roberto	Inputs Bytes/s	Outputs Bytes/s

Engineering Console

OPC Server



Ordering Information

Order No.	Engineering No.	Description
112020-5017	APP-SR1-PCU-C	applicom PCU1000 PCI Network Interface Card for Serial
112020-5018	APP-SR1-PCIE	applicom PCIE1000 PCI Express Network Interface Card for Serial
112026-0003	APP-INT-232-N	1x RS232 electrical interface without galvanic insulation
112026-0002	APP-INT-232-G	1x RS232 electrical interface with galvanic insulation
112026-0005	APP-INT-485-N	2x RS485/RS422 electrical interface without galvanic insulation
112026-0004	APP-INT-485-G	1x RS485/RS422 electrical interface with galvanic insulation

Windows[®] and the Windows logo are trademarks of the Microsoft group of companies PROFIBUS is a trademark of PROFIBUS International PCI Universal, PCI Express and the PCI Express logo are registered trademarks of PCI-SIG[®] Encompass is a trademark of Rockwell Automation

www.molex.com/link/bradnics.html